




Power Adaptors

12V Power Family		
Model Name	IS-PS20-12	IS-PM20L-12
Product Photo		
DC VOLTAGE	12V	12V
RATED CURRENT	1.67A	1.67A
RATED POWER	20W	20W
VOLTAGE ADJ. RANGE	11.4~12.6V	11.4~12.6V
VOLTAGE RANGE	90~264VAC	90~264VAC
FREQUENCY RANGE	47~63Hz	47~63Hz
AC CURRENT		
OVERLOAD	105~150% rated output power	105~150% rated output power
OVER VOLTAGE	16.8V	16.8V
WORKING TEMP.	-40~75°C	-40~75°C
WORKING HUMIDITY	10~90% RH non-condensing	10~90% RH non-condensing
STORAGE TEMP. HUMIDITY	-40 ~ +85°C, 10 ~ 95% RH	-40 ~ +85°C, 10 ~ 95% RH
DIMENSION	165*65*42mm (W*H*D)	230*68.1*44.6mm (W*H*D)

AC Power cord			
Model Name	CBL-AC-EU	CBL-AC-US	CBL-AC-JP
Product Photo			
Length	1.5m	1.5m	1.5m
Width	0.75mm ²	0.75mm ²	0.75mm ²
Voltage	300/500V	300/500V	300/500V

Lightning Protector

Lightning Protector			
Model Name	LPB-101G-P	LPB-101G	LPB-101
Product Photo			
100Mb Module			●
Gigabit Module	●	●	
Support PoE	●		
lightning surge	10/700us 6KV	10/700us 6KV	10/700us 6KV
Dimension	70 x 25 x 25mm (WxDxH)	70 x 25 x 25mm (WxDxH)	70 x 25 x 25mm (WxDxH)
Weight	0.03 Kg	0.03 Kg	0.03 Kg