





TYPE	DESCRIPTION	CODE	PRICE LIST	AVAILABILITY	
	<p>DALI Dimmer 12/48 Vdc</p>	<p>The DALI-2 1-channel dimmer EK-GD2-DL-1-LV allows the brightness control of low voltage LED sources from 12 to 48Vdc by means of PWM dimming. DALI-2 bus input reference IEC 62386. The 2-channel DALI-2 dimmer EK-GD2-DL-2-LV allows the control of brightness and colour temperature of low-voltage LED sources from 12 to 48Vdc by means of PWM dimming. Dynamic white temperature control TW DALI DT8, 2 independent channels (2 DALI addresses) or a single DALI DT6 channel. Functions can be set by means of a selector switch. Bus input DALI-2 reference IEC 62386.</p> <p>Main features</p> <ul style="list-style-type: none"> • Plastic housing • Free-standing device for installation in junction boxes or walls • Mounting on 35 mm profile rail (using special bracket code included) • IP10 degree of protection (device installed) 	<p>EK-GD2-DL-1-LV EK-GD2-DL-2-LV</p>	<p>CHF 85.00 CHF 104.00</p>	<p>Now available</p>
	<p>DALI Dimmer 90 230V~ 50/60Hz</p>	<p>The single-channel phase cut dimmer EK-GD2-DL-1-HV allows the brightness control of LED and halogen sources with a voltage of 90-230 Vac 50/60Hz for up to 220Watts. Input Bus DALI-2 reference IEC 62386 standard.</p> <p>Main features</p> <ul style="list-style-type: none"> • Plastic housing • Device for free installation in junction boxes or wall • Mounting on 35 mm profile rail (by means of code holder included) • IP10 degree of protection (device installed) 	<p>EK-GD2-DL-1-HV</p>	<p>CHF 99.00</p>	<p>Now available</p>

TYPE	DESCRIPTION	CODE	PRICE LIST	AVAILABILITY	
 <p>The image shows a white, rectangular DALI dimmer unit with a blue label. The label includes technical specifications: 'EK-GD1-DL-4-LV', 'Dimmer Dal PWM 12/48Vdc', 'DC In: 12-48V', and 'Out: 4x max 5A'. There are four numbered buttons (1-4) on the front panel and a power switch at the top.</p>	<p>DALI Dimmer 12/48Vdc 4 channels</p>	<p>The 4-channel DALI-2 dimmer allows control of brightness, temperature and RGBW colour of low-voltage LED sources. Power supply from 12 to 48Vdc, PWM dimming. Compliant with the new FLICKER-FREE standard. Input Bus DALI-2 reference IEC 62386 standard.</p> <p>Main features</p> <ul style="list-style-type: none"> • Plastic housing • Device with 4 modular units • IP20 degree of protection (device installed) 	<p>EK-GD1-DL-4-LV</p>	<p>CHF 229.90</p>	<p>Now available</p>
 <p>The image shows a white, rectangular DALI dimmer unit with a blue label. The label includes technical specifications: 'EK-GD1-DL-4-HV', 'Dimmer Dal 90-230V~ 50/60 Hz', 'Out: 4x 1 A', and 'Max Power: 7 A'. There are four numbered buttons (1-4) on the front panel and a power switch at the top.</p>	<p>DALI Dimmer 90- 230V~ 50/60hz 4 channels</p>	<p>The 4-channel DALI-2 dimmer allows brightness control of LED and halogen sources with voltage 90-230 Vac 50/60Hz for up to 200Watts on 4 channels each. Input Bus DALI-2 reference IEC 62386 standard.</p> <p>Main features</p> <ul style="list-style-type: none"> • Plastic housing • Device with 4 modular units • Mounting on 35 mm profile rail (according to EN 60715) • IP20 degree of protection (device installed) 	<p>EK-GD1-DL-4-HV</p>	<p>CHF 357.50</p>	<p>Now available</p>