

Item	Colour	Max Cable Bundle Dia.	L	W	Tensile LBS/kg
460251	BLACK	44	165	2.5	18/8



essentracomponents.com

© 2013 Essentra Components. All rights reserved. Registered in England, Company No. 547495. Registered Office: Avebury House, 201-249 Avebury Boulevard, Milton Keynes, MK9 1AU

Condition of Sale can be found on our website: essentra.com.

Essentra Components does not warrant that the files will be error free and may create new versions ("Upgrades") at any time, which may correct such errors. Essentra Components has no obligation to notify you of such upgrades. Any upgraded file will be published to the website, when it becomes available.

You are not permitted to load any of the files on to a network server for the purposes of distribution to one or more other computer(s) on that network or to effect such distribution. Essentra Components shall not be liable for any loss or damage whatsoever or however caused, arising directly or indirectly from the use of the files.

	UNL	ESS (OTHER	RWISE STATED		
ALL DIMENSIONS IN mm				DO NOT SCALE		
LINEAR TOLERANCE			CE	THIRD ANGLE PROJECTIO	N	
SIZE 0-10mm 10-30mm 30-50mm 50-100mm	(0) ±0.5 ±0.5 ±0.5	(0.0) ±0.15 ±0.20 ±0.30	(0.00) ±0.10 ±0.15 ±0.20 ±0.25			
100-200mm 200-300mm 300-500mm +500mm	±0.8 ±1.5 ±2.0 ±3.0 ±5.0	±0.50 ±0.80 ±1.20 ±2.00 ±3.00	±0.25 ±0.40 ±0.80 ±1.00 ±1.50	ANGULAR TOLERANCE ±0.5 DEGRE UNSPECIFIED RADII 0.25mm DRAFT ANGLE 0.5 DEGREES	ES	
ORG.SCALE	1.1			•		

NYLON

460251

UV-RESISTANT CABLE TIES

DWG.No.

ISSUE No. SR1767