



## Sockets

### PKNI 10 B



Product	PKNI 10 B
description	Pole terminal with claw edge, captive insulated head and insulated ring. 6 mm diameter nickel-plated brass threaded bolt with 2.6 mm diameter transverse hole. For insulated non-rotating installation in equipment chassis and switch panels up to 3.5 mm wall
operating instruction	BA402
article-no. / *colour	9301361xx  <span style="border: 1px solid black; padding: 2px;">Ni</span>
drawing	
technical data	
connection	M6 thread, solder connection
rated voltage <sup>(1)</sup>	30 VAC / 60 VDC
measurement cat. acc. to IEC 61010	O <sup>(3)</sup>
rated current <sup>(1)</sup> (consider derating curve)	63 A
material socket	brass, nickel plated
housing material	PA
temperature range acc. To IEC61010 <sup>(2)</sup>	-25 °C to +100 °C
flammability class acc. to UL 94 (only valid for basic material of housing)	V-2
standard	IEC 61010

4 mm system

- <sup>(1)</sup> for normal environmental conditions -5°C to +40°C  
<sup>(2)</sup> contact the manufacturer for applications at deviating temperature ranges  
<sup>(3)</sup> Other circuits that are not directly connected to mains  
stand: 03.09.2018